

# Model F2500

PROVEN AUTOMATIC ELECTRICAL TESTING SOLUTIONS



## ELECTRICAL PARAMETERS

<b>Continuity</b>		
Current	0.1mA to 1000mA	Programmable in 0.01mA steps (to 1mA), 1mA steps (>1mA)
Voltage Limit	1Vdc to 30Vdc	Programmable in 1V steps
<b>High Voltage DC</b>		
Voltage	25Vdc to 2500Vdc	Programmable in 1V steps
Current	Up to 4mA	
<b>High Voltage AC</b>		
Voltage	25Vrms to 1500Vrms	Programmable in 1V steps
Current	Up to 5mA	
Frequency	50Hz fixed	

## TYPICAL TEST PERFORMANCE

Continuity	0.05s per established connection 0.05s shorts test per point
Insulation and Hi-Pot	Programmable Ramp, Pre Dwell and Measure Dwell. Minimum 0.01s per point.

## MEASUREMENT

Continuity 4-Wire Mode	0.002Ω to 100kΩ	Accuracy 0.5% ±0.002Ω @ 1000mA	Resolution 0.001Ω
DC Insulation	5kΩ to 1000MΩ	Accuracy 5% ±0.5μA	

## OPTIONAL MODULES

AC Hi-Pot	1μA to 5000μA	Accuracy 10% including parasitic current	
Capacitance Module "CAP"	0pF to 1000pF	Basic Accuracy 5% ±5pF res1pF	Resolution 1pF
	1001pF to 3000pF	Basic Accuracy 5% ±10pF res10pF	Resolution 10pF
	3nF to 320nF	Basic Accuracy 5% ±2nF res0.1nF	Resolution 0.1nF
	0.3μF to 30μF	Basic Accuracy 5% ±2μF res1μF	Resolution 1μF
	Measurements include parasitic capacitance		
Capacitance & Inductance	0.001pF to 99,999μF	Basic Accuracy 0.02%	
Module "LCR"	0.01μH to 99,999H	Basic Accuracy 0.02%	
Temperature & Humidity Probe	1°C to 70°C	Accuracy ±0.5°C	Resolution 0.01°C
	0% to 100% RH	Accuracy ±2% RH	Resolution 0.03%
External Excitation Module (functional test switching)	EEMC5 (Changeover)	Current 5A	Points per card 16
	EEMD12 (Dual Bus)	Current 12A	Points per card 64
	Mswitch	Multibus architecture - See Model M1500	
	For Software controlled PSU options contact MK		

## SYSTEM OPTIONS

Continuity Current up to 2A, 5A or 10A
Continuity Range to 1MΩ
HV Resistance Range up to 5GΩ,10GΩ or 50GΩ
HVAC Frequency 60Hz fixed or to 400Hz variable
Fixed or Floating Earth Options.

## INTERFACE

32 off 2-Wire test points per board.
Maximum 512 Test Points per sub-rack.
Connection via high specification 37 way D-type sockets
Safety Interlock connection on front panel.
For custom front end connector options contact MK

## SUPPLY OPTIONS

115Vac 50/60Hz 1Ø
230Vac 50/60Hz 1Ø
415Vac 50/60Hz 3Ø

## LAYOUT OPTIONS

Standard 19" Rack Housing
Static Desktop or Mobile Ruggedised Cabinet
Single Station or Distributed Satellite Switching.

Under MK Test Systems Continuous Improvement Programme, Specifications are subject to change.