

**Looking For A High Power, Low Profile Power Supply?**

**KEPCO**

**Will Point You In The Right Direction!**



AN ISO 9001 COMPANY

**KEPCO**

THE POWER SUPPLIER™  
SINCE 1946

# You'll Always Find What You Need At Kepco



KLN Series Programmable Power Supply:  
750W 1U, Half-Rack (top), 1500W 1U, Full Rack (middle), 3000W 2U, Full Rack (bottom)

## KEPCO SERIES KLN - High Power, Low Profile, Many Models

The Kepco Series KLN is a new family of automatic crossover, low-profile, high-performance, low-cost programmable power supplies. The KLN Series offers stable d-c power in a 1U high, half-rack package for 750W, a 1U high, full-rack package for 1500W and a 2U high, full-rack package for 3000W. A total of 39 voltage-current combinations are offered. Output voltages range from 0-6 Volts to 0-600 Volts and output currents range from 0-400 Amps down to 0-1.25 Amps. Speed-controlled fans limit acoustic noise for bench-top applications when full power is not needed.

Precise programming of voltage, current and their limits may be achieved from the front panel, or by analog means or by RS 485 digital control. GPIB or LAN interfaces are factory-installed options.



For more information visit  
[www.kepcopower.com/kln.htm](http://www.kepcopower.com/kln.htm)

### MARKETS AND APPLICATIONS

- Aerospace and Satellite Test
- Telecom and IT Industry
- Automated Test Equipment
- Factory Automation
- QC Testing
- Burn-in
- Solar
- Water Purification
- Thermal Process Control
- Chemical Processing
- Semiconductor Manufacturing
- Battery Charging and Testing
- Electroplating, Sputtering and Coating
- New Energy R&D



Data subject to change without notice.  
© 2013 KEPCO, INC. Litho in USA

KEPCO, INC. • 131-38 Sanford Avenue • Flushing, NY 11355 USA • Tel: (718) 461-7000 • Fax: (718) 767-1102

Email: [hq@kepcopower.com](mailto:hq@kepcopower.com) • [www.kepcopower.com](http://www.kepcopower.com)

# 750 WATTS

**If you are looking for a high resolution (16 bit D/A for setting of voltage and current, 24 bit A/D for measurement), stable, quiet (speed-controlled fan) d-c power supply for your rack or bench, choose the 750W Series KLN.**

Front View  
1U High



Rear View



## KLN 750 WATT MODEL TABLE

MODEL (8) (9) (10)	D-C OUTPUT RANGE		RIPPLE (3)		LINE REGULATION (5) (11)		LOAD REGULATION (11)		RESPONSE TIME (7)			REMOTE SENSE VOLTAGE DROP (max)
	CV (1)	CC (2)	CV	CC (4)	CV	CC	CV (6)	CC (6)	FULL LOAD UP	FULL LOAD DOWN	NO LOAD DOWN	
	V d-c	A d-c	mV rms	mA rms	0.05% +mV	0.1% +mA	0.05% +mV	0.1% +mA	Sec	Sec	Sec	
KLN 6-100	0-6	0-100	10	180	2.8	11	2.8	23	0.08	0.05	0.6	1
KLN 8-90	0-8	0-90	10	180	2.8	11	2.8	23	0.08	0.05	0.6	1
KLN 12.5-60	0-12.5	0-60	10	120	4	8.5	4	18	0.08	0.05	0.8	1
KLN 20-38	0-20	0-38	10	76	4	5.8	4	12.6	0.08	0.05	0.8	1
KLN 30-25	0-30	0-25	10	63	5	4.5	5	10	0.08	0.08	0.9	1.5
KLN 40-19	0-40	0-19	10	48	6	3.9	6	8.8	0.08	0.08	1	2
KLN 50-15	0-50	0-15	10	43	8	3.6	8	8.2	0.08	0.08	1.1	2
KLN 60-12.5	0-60	0-12.5	10	38	8	3.25	8	7.5	0.08	0.08	1.1	3
KLN 80-9.5	0-80	0-9.5	10	29	10	2.95	10	6.9	0.15	0.15	1.2	4
KLN 100-7.5	0-100	0-7.5	10	23	12	2.75	12	6.5	0.15	0.15	1.5	5
KLN 150-5	0-150	0-5	16	18	17	2.5	17	6	0.15	0.15	2	5
KLN 300-2.5	0-300	0-2.5	25	13	32	2.25	32	5.5	0.15	0.15	3	5
KLN 600-1.25	0-600	0-1.25	75	8	62	2.13	62	5.26	0.25	0.3	4	5

- (1) Actual output voltage is  $\leq 0.1\%$  of rated voltage when output voltage is set to zero.
- (2) Actual output current is  $\leq 0.2\%$  of the rated current when output current is set to zero (resistive load).
- (3) Measured when output is within 10%-100% of rated value; ripple bandwidth: 300kHz (rms), noise bandwidth: <20MHz (p-p).
- (4) For 6V model: measured when output voltage 2-6V and rated current; all other models measured when output 10-100% of rated voltage and rated current.
- (5) Input voltage 100-240V a-c 50/60Hz, constant load.
- (6) Constant input voltage and output from no load to full load.
- (7) With rated input, resistive load output voltage changes from 10% to 90% or from 90% to 10%.
- (8) Rated power output with input 115V or 230V a-c
- (9) Specifications met after 30 minutes of operation, ambient temperature 23 $\pm$ 5 $^{\circ}$ C, humidity under 80% R. H, a-c input voltage nominal  $\pm 5\%$  of nominal, THD is 2%, not using the remote compensation, not operating in series or parallel.
- (10) Add G suffix for models with optional GPIB interface, add E suffix for optional LAN interface.
- (11) For example, the spec for KLN 6-100 line regulation and load regulation in CV mode is 0.05% + 2.8mV (or  $6 \times 0.0005 = +3\text{mV} + 2.8\text{mV} = 5.8\text{mV}$ ).

# 1500 WATTS

**If you are looking for a full rack, 1U, 1500 Watt d-c power supply which runs cool in your rack (with no air gap required between units) or on your bench, choose the 1500W Series KLN.**



Front View  
1U High



Close up of the bus bars  
with the protective cover



Rear View

## KLN 1500 WATT MODEL TABLE

MODEL (8) (9) (10)	D-C OUTPUT RANGE		RIPPLE (3)		LINE REGULATION (5) (11)		LOAD REGULATION (11)		RESPONSE TIME (7)			REMOTE SENSE VOLTAGE DROP (max)
	CV (1)	CC (2)	CV	CC (4)	CV	CC	CV (6)	CC (6)	FULL LOAD UP	FULL LOAD DOWN	NO LOAD DOWN	
	V d-c	A d-c	mV rms	mA rms	0.05% +mV	0.1% +mA	0.05% +mV	0.1% +mA	Sec	Sec	Sec	
KLN 6-200	0-6	0-200	15	360	2.8	18.5	2.8	38	0.08	0.05	0.6	1
KLN 8-180	0-8	0-180	15	360	2.8	18.5	2.8	38	0.08	0.05	0.6	1
KLN 12.5-120	0-12.5	0-120	15	248	3.4	14.5	4	28	0.08	0.05	0.8	1
KLN 20-76	0-20	0-76	15	152	4	9.6	4	20.2	0.08	0.05	0.8	1
KLN 30-50	0-30	0-50	15	125	5	7	5	15	0.08	0.08	0.9	1.5
KLN 40-38	0-40	0-38	15	95	6	5.8	6	12.6	0.08	0.08	1	2
KLN 50-30	0-50	0-30	15	85	7	5.2	7	11.4	0.08	0.08	1.1	2
KLN 60-25	0-60	0-25	15	75	8	4.5	8	10	0.08	0.08	1.1	3
KLN 80-19	0-80	0-19	15	57	10	3.9	10	8.8	0.15	0.15	1.2	4
KLN 100-15	0-100	0-15	15	45	12	3.5	12	8	0.15	0.15	1.5	5
KLN 150-10	0-150	0-10	24	45	12	3.5	12	8	0.15	0.15	2	5
KLN 300-5	0-300	0-5	38	25	32	2.5	32	6	0.15	0.15	3	5
KLN 600-2.5	0-600	0-2.5	113	15	62	2.26	62	5.5	0.25	0.3	4	5

See footnotes on 750 Watt Model Table, page 3.



KEPCO, INC. • 131-38 Sanford Avenue • Flushing, NY 11355 USA • Tel: (718) 461-7000 • Fax: (718) 767-1102

Email: [hq@kepcopower.com](mailto:hq@kepcopower.com) • [www.kepcopower.com](http://www.kepcopower.com)

# 3000 WATTS

If you are looking for a 3000 Watt programmable d-c power supply that operates on single phase input with active PFC meeting EN 61000-3-2:2006 Class A standards, choose the 3000W Series KLN.

Front View  
2U High



Rear View



## KLN 3000 WATT MODEL TABLE

MODEL (8) (9) (10)	D-C OUTPUT RANGE		RIPPLE (3)		LINE REGULATION (5) (11)		LOAD REGULATION (11)		RESPONSE TIME (7)			REMOTE SENSE VOLTAGE DROP (max)
	CV (1)	CC (2)	CV	CC (4)	CV	CC	CV (6)	CC (6)	FULL LOAD UP	FULL LOAD DOWN	NO LOAD DOWN	
	V d-c	A d-c	mV rms	mA rms	0.05% +mV	0.1% +mA	0.05% +mV	0.1% +mA	Sec	Sec	Sec	
KLN 6-400	0-6	0-400	23	1000	2.8	42	6.2	85	0.08	0.02	0.5	1
KLN 8-360	0-8	0-360	23	1000	2.8	42	6.2	85	0.08	0.02	0.5	1
KLN 12.5-240	0-12.5	0-240	23	800	3.2	29	7.1	60	0.08	0.1	0.8	1
KLN 20-150	0-20	0-150	23	600	4	18.5	8	38	0.08	0.1	0.8	1
KLN 30-100	0-30	0-100	23	310	5	13	9.5	27	0.08	0.16	0.9	1.5
KLN 40-76	0-40	0-76	23	250	6	10.5	11	22	0.08	0.16	1	2
KLN 50-60	0-50	0-60	23	200	7	9	13	19	0.08	0.16	1.1	2
KLN 60-50	0-60	0-50	23	150	8	7.5	14	16	0.08	0.16	1.1	3
KLN 80-38	0-80	0-38	23	110	10	6.2	17	13.4	0.15	0.3	1.2	4
KLN 100-30	0-100	0-30	23	90	12	5.3	20	11.6	0.15	0.3	1.5	5
KLN 150-20	0-150	0-20	36	90	17	4.2	27.5	9.4	0.15	0.3	2	5
KLN 300-10	0-300	0-10	57	50	32	3.1	50	7.2	0.15	0.3	3.5	5
KLN 600-5	0-600	0-5	170	30	62	2.55	95	6.1	0.25	0.5	4	5

(5) Input voltage: 190-240V a-c. 50/60Hz, constant load.

For others, see footnotes on 750 Watt Model Table, page 3.

## KLN INPUT SPECIFICATIONS

SPECIFICATION	RATING/DESCRIPTION	
Input Voltage	750 & 1500 Watt	100-240Vac, 50/60Hz
	3000 Watt	190-240Vac, 50/60Hz
Input Current (Full load)	750 Watt	8.1A@115V a-c; 4.1A@230V a-c
	1500 Watt	16.2A@115V a-c; 8.1A@230V a-c
	3000 Watt	15.6A@230V a-c
Inrush Current	750 Watt	12.5A@230V a-c
	1500 Watt	25A@230V a-c
	3000 Watt	50A@230V a-c
Power Factor (PF) Typical	750 & 1500 Watt	0.99 (at 115V a-c, rated output)
	3000 Watt	0.99 (at 230V a-c, rated output)
Efficiency	750 Watt	76% - 87%
	1500 Watt	77% - 88%
	3000 Watt	82% - 88%
Isolation Voltage	Input-Outputs	2000V a-c: 1 minute
	Input-Ground	2000V a-c: 1 minute
	Output-Ground (6V-150V)	350V d-c, leakage current: 100μA
	Output-Ground (300V-600V)	1200V d-c, leakage current: 100μA



Parallel connection of two identical KLN power supplies (up to five possible) using optional Parallel Socket Board 536-0129 and Programming Port Cable 518-0119



Series connection of two identical KLN power supplies using optional Series Socket Board 536-0130 and Programming Port Cable 518-0119

## KLN OUTPUT SPECIFICATIONS

SPECIFICATION	RATING/DESCRIPTION	
Type of Stabilizer	Constant Voltage (CV)/Constant Current (CC), automatic crossover	
Adjustment Range	Voltage	0 to 100% of rated voltage
	Current	0 to 100% of rated current
Protective Functions	Programmable overvoltage (OVP) Programmable overcurrent (OCP) Overtemperature (OTP) Fuse blown	
Protection Setting Range	Overvoltage	0% to 110% of rated voltage
	Overcurrent	0% to 110% of rated current
Remote Error Sense Compensation	5V max. (See Applicable Model Table)	
Parallel Operation	Up to 5 units maximum, automatic load sharing	
Series Operation	2 units maximum (total voltage must not exceed 600V)	
Temperature, Coefficient	Constant Voltage Mode Constant Current Mode	100ppm/°C of rated output voltage or current, after 30 minute warm-up
Time Drift	Constant Voltage Mode Constant Current Mode	0.05% of rated output voltage or current over 8 hrs interval following 30 minutes warm-up. Constant line, load and temperature.
Transient	Constant Voltage Mode	20V and under: ≤1.5ms;
		30V-100V: ≤1ms
		150V-600V: ≤2ms



## KLN PROGRAMMING CHARACTERISTICS - LOCAL

SPECIFICATION		RATING/DESCRIPTION
Local Control		Rotary encoder
Setting Resolution	Voltage & Current	4 digits
Display Resolution	Voltage & Current	4 digits
Setting Accuracy	Voltage	$\pm 0.1\% \pm 3C^{(1)}$ at rated voltage
	Current	$\pm 0.5\% \pm 3C^{(1)}$ at rated current
Display Reading Accuracy	Voltage	$\pm 0.2\% \pm 3C^{(1)}$ at rated voltage
	Current	$\pm 0.5\% \pm 3C^{(1)}$ at rated current
Overvoltage Protection		Programmable, 0 to 110% of rated voltage
Overcurrent Protection		Programmable, 0 to 110% of rated current

(1) C = 1 count of the last displayed digit.



Analog Interface  
RS 485 Interface  
(Standard)



LAN Interface  
(Optional) Added



GPIB (IEEE 488) Interface  
(Optional) Added

## KLN PROGRAMMING CHARACTERISTICS - DIGITAL

SPECIFICATION		RATING/DESCRIPTION
Command Setting Resolution		$\pm 0.002\%$ of full scale
Command Readback Resolution		$\pm 0.002\%$ of full scale
Command and D/A Setting Accuracy	Voltage	$\pm 0.1\% \pm 3C^{(1)}$ at rated voltage
	Current	$\pm 0.5\% \pm 3C^{(1)}$ at rated current
Command and A/D Measurement Accuracy	Voltage	$\pm 0.2\% \pm 2C^{(1)}$ at rated voltage (Average Measurement)
	Current	$\pm 0.5\% \pm 3C^{(1)}$ at rated current (Average Measurement)
Command Response Time		$\leq 20\text{ms}$ (After received) <sup>(2)</sup>
RS-485 Digital Interface (Standard)		Default baud rate: 115.2K Baud rates: 4.8K, 9.6K, 19.2K, 38.4K, 57.6K, 115.2K user selectable Max number of units connected to bus: 254 Max. effective control distance: 1000 meters
GPIB IEEE 488.2 Digital Interface		Optional (G suffix)
LAN Digital Interface		Optional (E suffix)

(1) C = 1 count of the last displayed digit.

(2) Programming time = Command response time + Output response time. The output response time differs for different models, from 30mS ~ 200mS.

## KLN PROGRAMMING CHARACTERISTICS - ANALOG

SPECIFICATION		RATING/DESCRIPTION
Analog Setting Accuracy Constant Voltage Mode (CV)	Voltage	$\pm 5\%$
	Current	$\pm 5\%$
Analog Setting Accuracy Constant Current Mode (CC)	Voltage	$\pm 5\%$
	Current	$\pm 5\%$
Analog Monitor Accuracy	Rated voltage output	$10.00\text{V} \pm 0.25\text{V}$
	Zero voltage output	$0.00\text{V} \pm 0.25\text{V}$
	Rated current output	$10.00\text{V} \pm 0.25\text{V}$
	Zero current output	$0.00\text{V} \pm 0.25\text{V}$

## KLN PHYSICAL SPECIFICATIONS

SPECIFICATION	RATING/DESCRIPTION	
Weight	750 Watt	11.2 lbs (5.1 Kg)
	1500 Watt	20.3 lbs (9.2 Kg)
	3000 Watt	33.2 lbs (15.1 Kg)
Dimensions W x H x D	750 Watt	8.46" x 1.73" x 18.5" (215mm x 44mm x 470mm)
	1500 Watt	16.93" x 1.73" x 18.5" (430mm x 44mm x 470mm)
	3000 Watt	16.93" x 3.46" x 18.5" (430mm x 88mm x 470mm)
Source Power Connector	750 Watt	IEC 320 inlet
	1500 & 3000 Watt	3-position terminal block
Load Connections	6V to 100V models	± bus bars with protective cover
	150V to 600V models	(750W) 5-position Euroblock
	150V to 600V models	(1500W & 3000W) 4-position terminal block
Programming Control port	26-pin connector (mating connector supplied)	
SER IN port	2-position Euroblock (mating connector supplied)	
Sense port	3-position Euroblock (mating connector supplied)	
RS-485 port	3-position Euroblock (mating connector supplied)	
LAN port (optional)	RJ 45 connector	
GPIB port (optional)	Standard IEEE 488.2 GPIB connector	

## KLN GENERAL (ENVIRONMENTAL) SPECIFICATIONS

SPECIFICATION	RATING/DESCRIPTION	
Temperature	Operating	0 to 50°C (indoor use)
	Storage	-20 to +70°C
Humidity	Operating	30%~90% RH (no condensation)
	Storage	10%~90% RH (no condensation)
Altitude	3000m max	
Cooling	Speed-Controlled Fan	
Acoustic Noise	<70 dB (A)	
EMC Emissions (EN 61326-1)	Conducted Disturbance	EN 55011:2007 + A2:2007 Class B
	Radiated Disturbance	EN 55011:2007 + A2:2007 Class B
	Harmonic Distortion	EN 61000-3-2:2006 Class A
	Voltage Fluctuations and Flicker	EN 61000-3-3:2008 Section 5
EMC Immunity (EN 61326-1)	Electrostatic Discharge (ESD)	EN 61000-4-2:2009 Class B
	Radiated RF Magnetic Field	EN 61000-4-3:2006 + A1:2008 + A2:2010 Class A
	Electrical Fast Transients and Bursts	EN 61000-4-4:2004 + A1:2010 Class B
	Surge	EN 61000-4-5:2006 Class B
	Conducted Disturbance Induced by RF Fields	EN 61000-4-6:2009, Class A
	Voltage Dips and Short Interruptions	EN 61000-4-11:2004, Class C

NOTE: All specifications apply after power on for 30 minutes, ambient temperature: 23±5°C, Humidity: under 80% RH, AC Voltage: ±5%, Frequency: ±5%.

For more information visit [www.kepcopower.com/klm.htm](http://www.kepcopower.com/klm.htm)

## Looking For More High Power, Low Profile Power Supplies?

### SERIES KLR



Kepeco introduces Series KLR, offering 2400 Watts of stable, controllable d-c power in the industry standard 1U package. Five models from 20 Volts to 300 Volts are available with a conventional rectangular operating area. Input is 185-264V a-c, single phase. GPIB, RS232 and isolated analog programming are all standard, LXI Ethernet is a factory installed option replacing RS232.

[www.kepcopower.com/klr.htm](http://www.kepcopower.com/klr.htm)

### SERIES KLP



Using high-frequency switch-mode topology for high efficiency and small size, the KLP provides 1200 watts of well-regulated, controllable d-c power in a 1U (1.75 inch high) by 19 inch rack-mountable package. KLP replaces the need for multiple power supplies by expanding the operating region. The breakthrough of a hyperbolic power limit delivers a full 1200 Watts over an expanded operating range, not just the conventional rectangular operating area.

[www.kepcopower.com/klp.htm](http://www.kepcopower.com/klp.htm)



KEPCO, INC. • 131-38 Sanford Avenue • Flushing, NY 11355 USA • Tel: (718) 461-7000 • Fax: (718) 767-1102

Email: [hq@kepcopower.com](mailto:hq@kepcopower.com) • [www.kepcopower.com](http://www.kepcopower.com)