



SP Series 600W Programmable DC Power Supply

SP Series 600W programmable DC power supply has the features including high precision and resolution, high efficiency low ripple, complete multiple protection, Master/Slave Series/Parallel modes, and multiple communication interfaces, which allow a more flexible and convenience use of the power supply.



- *600W / 1U high power density.
- *Master /slave parallel & series operation modes for up to 4 units.
- *With accurate voltage and current measurement capability.
- *High-speed programmable interface.
- *Coded knob, multifunctional keyboard.
- *Freely switchover between constant voltage (CV) and constant current (CC) operating modes.
- *Voltage rate of rise and drop functions.
- *Equips with LIST waveform editing function.
- *Protection functions: OVP, OCP, OPP, SCP and OTP.
- *Standard RS232, RS485, LAN and USB communication interfaces (ports).
- *Use the Standard Commands for Programmable Instrumentation (SCPI) communication protocol.
- *Standard analog external remote inputs.
- *Remote sensing line voltage-drop compensation.
- *DVM independent measurement function.
- *Have obtained CE, UL, CSA ,FCC and other certifications.



| Model | SP20VDC600W | SP32VDC600W | SP40VDC600W | SP60VDC600W | SP75VDC600W |
|---------------------------------|--|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Input Voltage Range | 90~265VAC | 90~265VAC | 90~265VAC | 90~265VAC | 90~265VAC |
| Input Frequency Range | 47~63Hz | 47~63Hz | 47~63Hz | 47~63Hz | 47~63Hz |
| Power Factor | >0.98 | >0.98 | >0.98 | >0.98 | >0.98 |
| Output Power Range | 0~600W | 0~600W | 0~600W | 0~600W | 0~600W |
| Output Voltage Range | 0~20V | 0~32V | 0~40V | 0~60V | 0~75V |
| Output Current Range | 0~60A | 0~50A | 0~40A | 0~25A | 0~20A |
| Voltage Display resolution | 0.1mV | 0.1mV | 0.1mV | 0.1mV | 0.1mV |
| Current Display Resolution | 0.2mA | 0.2mA | 0.2mA | 0.2mA | 0.2mA |
| Voltage Programmable Resolution | 1.5mV | 1.5mV | 1.5mV | 1.5mV | 1.5mV |
| Current Programmable Resolution | 2mA | 2mA | 2mA | 1mA | 1mA |
| Voltage Setting Accuracy | 0.05%+15mV | 0.05%+15mV | 0.05%+15mV | 0.05%+15mV | 0.05%+15mV |
| Current Setting Accuracy | 0.1%+60mA | 0.1%+50mA | 0.1%+40mA | 0.1%+25mA | 0.1%+20mA |
| Voltage Measurement Accuracy | 0.05%+15mV | 0.05%+15mV | 0.05%+15mV | 0.05%+15mV | 0.05%+15mV |
| Current Measurement Accuracy | 0.1%+60mA | 0.1%+50mA | 0.1%+40mA | 0.1%+25 mA | 0.1%+20mA |
| Voltage Ripple | 40mVp-p/6mVrms | | | | |
| Current Ripple | 60mA(Full Range) 20mA(TYP value) | 50mA(Full Range) 20mA(TYP value) | 40mA(Full Range) 20mA(TYP value) | 25mA(Full Range) 10mA(TYP value) | 20A(Full Range) 10mA(TYP value) |
| Voltage Load Regulation | 10mV | 10mV | 10mV | 10mV | 10mV |
| Current Load Regulation | 60mA | 50mA | 40mA | 25mA | 20mA |
| Line Voltage Regulation | 0.005%+1mV | 0.005%+1mV | 0.005%+1mV | 0.005%+1mV | 0.005%+1mV |
| Line Current Regulation | 4mA | 4mA | 4mA | 4mA | 4mA |
| Voltage Temperature Coefficient | 100ppm/°C | | | | |
| Current Temperature Coefficient | 150ppm/°C | | | | |
| DVM Resolution | 0.1mV | 0.1mV | 0.1mV | 0.1mV | 0.1mV |
| DVM Accuracy | 0.05%+15mV | 0.05%+15mV | 0.05%+15mV | 0.05%+15mV | 0.05%+15mV |
| Operating Mode | Constant voltage (CV) / Constant Current (CC) | | | | |
| Remote Compensation | 4V MAX | | | | |
| Response (Voltage Rise) | ≤10ms | ≤12ms | ≤15ms | ≤10ms | ≤10ms |
| Response (Voltage Drop) | ≤150ms(No Load) ≤20ms(Full Load) | ≤150ms(No Load) ≤20ms(Full Load) | ≤150ms(No Load) ≤20ms(Full Load) | ≤100ms(No Load) ≤20ms(Full Load) | ≤100ms(No Load) ≤20ms(Full Load) |
| Load Transient Recovery Time | ≤2ms | ≤2ms | ≤2ms | ≤2ms | ≤2ms |
| Command Respond Time | 50ms | 50ms | 50ms | 50ms | 50ms |
| Efficiency (Full Load) | 82.5% | 86% | 87% | 88% | 88% |
| Communication Modes | RS232/RS485/USB/LAN | | | | |
| Protection Functions | OVP/OCP/OTP/OPP/SCP protection functions | | | | |
| Net Weight | 9.2kg | 9.2kg | 9.2kg | 8.9kg | 8.9kg |
| Weight of Accessories | 0.8kg | 0.8kg | 0.8kg | 0.8kg | 0.8kg |
| Dimensions (W x H x D) | 483.0x44.0x531.0 mm | | | | |
| Operating Environment | Temperature: 0°C ~ 40°C Relative humidity 10%-90%(non-condensing) | | | | |
| Cooling | Forced air-cooling | | | | |
| Certification | CE/UL/CSA/FCC | | | | |

APM Technologies (Dongguan) Co., Ltd

Add: #7, Link Information Industry Park, Shuilianshan Road,
Nancheng, Dongguan, Guangdong, China

Tel:+86 769-2202 8588 Fax:+86 769-2202 6771

E-mail:mk@apmtech.cn Web:en.apmtech.cn



| Model | SP150VDC600W | SP200VDC600W | SP400VDC600W | SP600VDC600W | SP800VDC600W |
|---------------------------------|--|-------------------------------------|--------------------------------------|---------------------------------------|---------------------------------------|
| Input Voltage Range | 90~265VAC | 90~265VAC | 90~265VAC | 90~265VAC | 90~265VAC |
| Input Frequency Range | 47~63Hz | 47~63Hz | 47~63Hz | 47~63Hz | 47~63Hz |
| Power Factor | >0.98 | >0.98 | >0.98 | >0.98 | >0.98 |
| Output Power Range | 0~600W | 0~600W | 0~600W | 0~600W | 0~600W |
| Output Voltage Range | 0~150V | 0~200V | 0~400V | 0~600V | 0~800V |
| Output Current Range | 0~10A | 0~8A | 0~7.5A | 0~5A | 0~4A |
| Voltage Display resolution | 1mV | 1mV | 1mV | 1mV | 1mV |
| Current Display Resolution | 0.2mA | 0.1mA | 0.1mA | 0.1mA | 0.1mA |
| Voltage Programmable Resolution | 3mV | 3mV | 8mV | 12mV | 16mV |
| Current Programmable Resolution | 1mA | 1mA | 1mA | 1mA | 1mA |
| Voltage Setting Accuracy | 0.1%+15mV | 0.1%+15mV | 0.05%+100mV | 0.05%+150mV | 0.05%+200mV |
| Current Setting Accuracy | 0.1%+10mA | 0.1%+8mA | 0.1%+20mA | 0.1%+16mA | 0.1%+10mA |
| Voltage Measurement Accuracy | 0.1%+15mV | 0.1%+15mV | 0.05%+100mV | 0.05%+150mV | 0.05%+200mV |
| Current Measurement Accuracy | 0.1%+10mA | 0.1%+8mA | 0.1%+20mA | 0.1%+16mA | 0.1%+10mA |
| Voltage Ripple | 120mVp-p/40mVrms | | 180mVp-p/80mVrms | | |
| Current Ripple | 40mA(Full Range) 10mA(TYP value) | 40mA(Full Range) 10mA(TYP value) | 40mA(Full Range) 10mA(TYP value) | 40mA(Full Range) 10mA(TYP value) | 40mA(Full Range) 10mA(TYP value) |
| Voltage Load Regulation | 15mV | 15mV | 30mV | 30mV | 40mV |
| Current Load Regulation | 10mA | 8mA | 20mA | 16mA | 10mA |
| Line Voltage Regulation | 0.02%+8mV | 0.02%+8mV | 0.02%+20mV | 0.02%+30mV | 0.02%+40mV |
| Line Current Regulation | 10mA | 30mA | 10mA | 8mA | 10mA |
| Voltage Temperature Coefficient | 100ppm/°C | | | | |
| Current Temperature Coefficient | 150ppm/°C | | | | |
| DVM Resolution | 1mV | 1mV | 8mV | 12mV | 16mV |
| DVM Accuracy | 0.1%+15mV | 0.1%+15mV | 0.05%+100mV | 0.05%+150mV | 0.05%+200mV |
| Operating Mode | Constant voltage (CV) / Constant Current (CC) | | | | |
| Remote Compensation | 4V MAX | | | | |
| Response (Voltage Rise) | ≤25ms | ≤30ms | ≤60ms | ≤60ms | ≤60ms |
| Response (Voltage Drop) | ≤400ms(No Load) ≤32ms(Full Load) | ≤600ms(No Load) ≤50ms(Full Load) | ≤800ms(No Load) ≤100ms(Full Load) | ≤1200ms(No Load) ≤100ms(Full Load) | ≤1200ms(No Load) ≤100ms(Full Load) |
| Load Transient Recovery Time | ≤2ms | ≤3ms | ≤3ms | ≤3ms | ≤3ms |
| Command Respond Time | 50ms | 50ms | 50ms | 50ms | 50ms |
| Efficiency (Full Load) | 88% | 88% | 88% | 88% | 88% |
| Communication Modes | 1. RS232/RS485/USB/LAN; 2. RS232/RS485/USB/LAN/GPIB | | | | |
| Protection Functions | OVP/OCP/OTP/OPP/SCP protection functions | | | | |
| Net Weight | 9.5kg | 9.5kg | 9.5kg | 9.5kg | 9.5kg |
| Weight of Accessories | 1.0kg | 1.0kg | 1.0kg | 1.0kg | 1.0kg |
| Dimensions (W x H x D) | 483.0x44.0x531.0 mm | | | | |
| Operating Environment | Temperature: 0°C ~ 40°C Relative humidity 10%-90%(non-condensing) | | | | |
| Cooling | Forced Cooling | | | | |
| Certification | CE/UL/CSA/FCC | | | | |

APM Technologies (Dongguan) Co., Ltd

Add: #7, Link Information Industry Park, Shuilianshan Road,
Nancheng, Dongguan, Guangdong, China

Tel:+86 769-2202 8588 Fax:+86 769-2202 6771

E-mail:mk@apmtech.cn Web:en.apmtech.cn