

Product Brief

# VIavi

## IFF-45TS

### MK XIIA and TACAN Bench Test Set

A leading edge RF signal generator/receiver designed for engineering manufacturing and return-to-service applications

The IFF-45TS test set provides RF signal generation and parametric measurement of MK XIIA and TACAN equipment. Replies and interrogations can be individually configured to support testing requirements. ADS-B Out testing monitors ADS-B, TIS-B, ADS-R and Acquisition squitters. The IFF-45TS emulates either a TACAN ground transponder or a TACAN airborne interrogator, providing six TACAN test modes.

For a fully configurable automated test solution using the IFF-45TS as the RF source, see the VIavi Solutions IFF-7300S Series Automated Test System.



### Features

- MK XIIA AIMS certified for Level 1 and Level 2
- Supports DoD AIMS 04-900A Option A – KIV-78 & QRTK6 NG (with Airbus DS QRTK6 NG adapter) and Option B – KIV-77 & SIT-2010 crypto appliquéés (part number 72438 only)
- Dual I/O for diversity testing of transponders or SUM/DIFFERENCE on interrogators
- Separate connections for direct or over-the-air testing
- Software defined radio design allows waveform flexibility and future growth potential
- Dual signal generator design allows coordinated signal production for interference and echo testing
- Remote interfaces consist of RS-232, Ethernet and GPIB
- Graphical User Interface (GUI) allows easy access to test features
- Test ranges of up to 3 km with appropriate antennas

### Applications

- Engineering – Development and qualification testing for MK XIIA, ADS-B Beacon, and TACAN equipment
- Manufacturing – factory calibration and verification testing
- Depot/Service – Level 1 and 2 return-to-service testing
- Support for DO-260B, AIMS 03-1000B, Amendment 1 and DO-181E certification testing
- Over-the-air platform testing of MK XIIA equipment including Mode 5, ADS-B beacons and TACAN interrogators
- Industry-wide use for development and end item testing of transponders and interrogators

## Ordering Information

### Versions and Options

| Order Number | Description  |
|--------------|--|
| 72438        | IFF-45TS Transponder Modes 1,2,3/A,4 (Internal Crypto),C,S (Mode 5 capable)                        |
| 72439        | IFF-45TS-A Transponder Modes 1,2,3/A,4 (Internal Crypto),C,S                                       |
| 140612       | SERD 65A08, Kit, IFF-45TS Test Set   |
| 83404        | 45TSOPT1 IFF Transponder Mode 5 (for use with Order Number 72438 only)                             |
| 83405        | 45TSOPT2 Interrogator Modes 1,2,3/A,C,S,4  |
| 83406        | 45TSOPT3 IFF Interrogator Mode 5 (for use with Order Number 72438 only, requires option 2 (83405)) |
| 83407        | 45TSOPT4 DME/TACAN   |
| 91684        | 45TSOPT5 ADS-B Out   |
| 140608       | 45TSOPT10 ADS-B Out Integrity Test App   |
| 112120       | Kit, ADS-B Out (fielded units), IFF-45TS   |
| 112364       | Kit, ADS-B Out (fielded units), IFF-45TS-A   |

### NSN Information

|                  |                                     |
|------------------|-------------------------------------|
| 6625-01-617-2567 | IFF-45TS w/options 1, 2, 3, 6, 8, 9 |
| 6625-01-611-6485 | IFF-45TS w/options 2 and 8          |

### Standard Accessories

|                   |  |
|-------------------|--|
| 92053             | PC Windows-based GUI (IFF45TS)         |
| 92054             | Operation Manual (CD) (IFF45TS)        |
| 6138              | Getting Started Manual (IFF45TS)       |
| 92053             | PC Windows-based GUI (IFF45TS-A)       |
| 92054             | Operation Manual (CD) (IFF45TS-A)      |
| 6141              | Getting Started Manual (IFF45TS-A)     |
| 62302* or 62315** | AC power cord, *110V or **220V         |
| 30050             | Serial data cable, 9 pin D, 1.5 meters |

### Extended Warranty (2 year standard)

|       |                                      |
|-------|--------------------------------------|
| 84363 | 36 months with scheduled calibration |
| 84364 | 60 months with scheduled calibration |

### Export Control and Warning

VIAMI Solution's military products are controlled for export under the International Traffic in Arms Regulations (ITAR). A license from the U.S. Department of State is required prior to the export of this product from the United States. This product may not be sold or proposed or offered for sale to certain countries including: Belarus, Burma, China, Cuba, Haiti, Iran, Liberia, Libya, North Korea, Somalia, Syria, Sudan, and Vietnam. See ITAR 126.1 for complete information.



Contact Us +1 316 522 4981  
AvComm.Sales@viavisolutions.com

To reach the VIAMI office nearest you, visit  
viavisolutions.com/contact.

© 2018 VIAMI Solutions Inc.  
Product specifications and descriptions in this document are subject to change without notice.  
IFF-45TS-pb-avi-nse-ae  
30187399 900 0918

### Optional Accessories

|         |   |
|---------|---|
| 88631   | 45TSOPT6 KIV 77 adapter (Opt B)                   |
| 89879   | 45TSOPT8 KIT/KIR-1A/C adapter                     |
| 86075   | 45TSOPT9 KIV 78/KIV 6 adapter (Opt A)             |
| 63975   | Controller w/ touch-screen monitor, w/ Mode 5 GUI |
| 140416  | Controller w/ touch-screen monitor, w/ Mode 4 GUI |
| 112349  | UC-584 coupler kit, dual antenna                  |
| 112350  | UC-584 coupler kit, single antenna                |
| 138553  | Kit, Laptop with IFF45TS Mode 4 GUI               |
| 138552  | Kit, Laptop with IFF45TS Mode 5 GUI               |
| 138512  | Transit Case, IFF45TS                             |
| 93023** | IFF45TS Maintenance Manual                        |
| 89345** | IFF45TS-A Maintenance Manual                      |
| 91771   | Antenna   |

\*\*Includes remote program GUI

### Physical Characteristics

|                        |   |
|------------------------|---|
| Size:<br>Test Set Only | 4"H x 17.75"W x 21"D<br>(10 cm x 45 cm x 53 cm) |
| Weight                 | 24 lbs. (10 kg)                                 |

### Environmental

|                   |                                 |
|-------------------|---------------------------------|
| Operational Temp. | -10° to +55°C (+14° to +131° F) |
| Storage Temp.     | -10° to +55°C (+14° to +131° F) |

### Test Set Certifications

|  |
|--|
| UL   |
| CE   |
| DoD AIMS MK XIIA Level 1 and Level 2                             |
| For complete certification list see IFF-45TS Specification Sheet |