



## High Performance Air Dryer

### DATA & SPECIFICATIONS

Dryer Type Heat-less Regenerative Desiccant

### WEIGHTS & DIMENSIONS

Height 25-3/4" (65.40 cm), with feet: 26-1/4" (66.75 cm)

Width 16" (40.64 cm)

Depth 5-1/4" (13.33 cm), with feet: 7-1/2" (19.05 cm)

Inlet Connection 1/2" O.D. (SMC push-in style)

Outlet Connection 1/2" O.D. (SMC push-in style)

### AIR INPUT REQUIREMENTS

Clean Dry Air (CDA)

Oil Content 0.8 ppm or better

Filter Rating 0.3 micron or better

Dewpoint <10°C @ 6.2 BAR (90 PSI)

Supply Pressure 90 to 110 PSIG

Air Flow 24 scfm

### AIR OUTPUT PERFORMANCE

Dewpoint <-70°C @ 6.2 BAR (90 PSI)

Air Pressure input pressure minus 8 PSIG

Air Flow 20scfm

### POWER REQUIREMENTS

Available Configurations\*

115v, 60Hz

230v, 50Hz

208 - 220v, 60Hz

\*Power Requirements are specified at the time of your order. High Performance Air Dryers are equipped with the required line cord and plug.



The inTEST Thermal family includes three temperature-related corporations: Temptronic, Sigma Systems, and Thermonics.

